



## NLT4MD-V

4 pole male chassis connector, metal housing, vertical PCB mount, self tapping screw holes (A-screw)

The speakON STX Series was especially designed for heavy duty amplifier-loudspeaker applications like professional touring. The extremely rugged and durable STX Series features an all metal housing.

### Features & Benefits

- Extremely robust metal housing designed for harsh and demanding environment
- Current rating 40 Amp continuous, 50 Amp audio with 50% duty cycle
- Mates with all currently available speakON products
- 4 pole version has UL Recognized components, CSA listed
- Ideal product for touring applications and harsh environments
- Uses precise "Quick Lock" system
- Weatherproof built-in gasket meets IP 54 protection class in mated condition
- 4 type range - also male cable connector and female receptacle on 4-pole version

## Technical Information

Product	
<b>Title</b>	NLT4MD-V
<b>Connection Type</b>	speakON
<b>Gender</b>	male

Electrical	
<b>Contact resistance</b>	< 2 mΩ (after lifetime)
<b>Dielectric strength</b>	4 kVdc (peak)
<b>Insulation resistance</b>	> 10 GΩ
<b>Rated current per contact</b>	40 A rms continuous
<b>Rated current per contact</b>	50 A audiosignal, duty cycle 50 %
<b>Rated voltage</b>	250 V ac
<b>Attention</b>	speakON is NOT to be used as an AC mains or power supply connector!

Mechanical	
<b>Lifetime</b>	> 5000 mating cycles
<b>Wiresize</b>	
<b>Wiring</b>	vertical PCB mount
<b>Locking device</b>	Quick Lock
<b>Mounting direction</b>	Rear mounting
<b>Chassis shape</b>	square G-size flange
<b>Layout</b>	self tapping screw holes (A-Screw)

Material	
<b>Contact plating</b>	4 µm Ag
<b>Insert</b>	Polyamide (PA 6 30 % GR)
<b>Shell</b>	Zinc diecast (ZnAl4Cu1) Ni
<b>Contacts</b>	Spring Copper (CuSn0.2)

Environmental	
<b>Flammability</b>	UL 94 HB
<b>Protection class</b>	IP 54 (mated condition)
<b>Solderability</b>	Complies with IEC 68-2-20
<b>Temperature range</b>	-30 °C to +80 °C